



# Solid Stain Shingles

## Warranty Information



A green generation caring for environment 

### Characteristics

Water based 

Kiln-dried

Resquared and Rebutted (R&R)

Solid stain (1,2 or 3 coats)

80 times less VOC's than maximum allowed LEED certification.

**50** Years Against Wood Decay

	Opaque	Translucent
<b>ATL 3 coats*</b>	<b>25</b> Years	
<b>ATL 2 coats**</b>	<b>15+15</b> Years	<b>5+5</b> Years
<b>2 coats 2 sides</b>	<b>25</b> Years	
<b>1 coat 2 sides</b>	<b>10+10</b> Years	<b>5+5</b> Years

\*1 coat primer on all sides + 2 coats on 4 sides.

\*\* 1 coat primer on all sides + 1 coat on 4 sides.

### Warranty Applicability:

The instructions for installation must be respected.

Walls application only.

No warranty if shingles is installed in direct contact with the ground.

See detailed warranty for more informations.



## Technical Specifications

### Shingle dimensions

Butt thickness: 3/8" (9.5mm)  
 Width: 3 1/2" (89mm) to 11" (279mm)  
 Length: 16" (406mm)

### Packaging

Packaging type: Box  
 Box dimensions: 20 1/4" x 16 1/2" x 10 1/4"  
 (514mm x 419mm x 260mm)  
 Box weight: 28 lbs  
 Box qty per pallet/truck space: 40  
 Truck space dimensions: 88" x 42" x 42"  
 (223.5cm x 107cm x 107cm)  
 Truck space weight: 1400 lbs

### Characteristics

Water based   
 Kiln-dried  
 Resquared and Rebutted (R&R)  
 Excellent UV protection  
 Solid stain (1,2 or 3 coats)  
 42 VOC 6 time less then leed allowed standard.

### Warranty

10 + 10 years for 1 coat  
 15 + 15 years for **Atlantic 2 coats**  
 25 years for **Atlantic 3 coats**  
 50 Years on wood decay

## Solid Stains



### Colors



Box



Pallet / Truckspace

